



Übersicht Aktivkohlefilter

	Typ	Bild	max. Durchsatz	AK-Volumen ca.	Dimensionen ca.	Anwendungen
Luft- / Gasfilter	L1500		1.500 m³/h	1,5 m³	DxH [mm] 1.200 x 2.250	→ Abluft → Gerüche
	L4000		3.000 m³/h	3,0 m³	DxH [mm] 1.700 x 2.250	→ Abluft → Gerüche
	L6000		6.000 m³/h	5,0 m³	DxH [mm] 2.300 x 2.400	→ Abluft → Gerüche
	G500		500 m³/h	1,0 m³	DxH [mm] 1.000 x 2.150	→ Abluft / Abgas → Biogas / Klärgas → Gerüche
	G1000		1.000 m³/h	2,0 m³	DxH [mm] 1.300 x 2.350	→ Abluft / Abgas → Biogas / Klärgas → Gerüche
	G1500		1.500 m³/h	3,0 m³	DxH [mm] 1.600 x 2.500	→ Abluft / Abgas → Biogas / Klärgas → Gerüche
	L20000M		20.000 m³/h	14,0 m³	LxBxH [mm] 6.000x2.400x2.600	→ Abluft → Gerüche
Flüssigkeitsfilter	W1200D		15 m³/h	2,0 m³	DxH [mm] 1.300 x 2.400	→ Produktveredelung → Wasser / Abwasser
	W4000F		25 m³/h	3,0 m³	DxH [mm] 1.600 x 2.500	→ Wasser / Abwasser
	W20000M		70 m³/h	Max. 20,0 m³	DxH [mm] 2.500 x 7.200	→ Wasser / Abwasser
	W25000		80 m³/h	Max. 25,0 m³	DxH [mm] 2.600 x 7.800	→ Wasser / Abwasser